

# EDAN

NEW



## DUS 8

### Digital Ultrasonic Diagnostic Imaging System

DUS 8, EDAN's new member of the all digital ultrasonic diagnostic imaging systems, not only endeavors to offer the most competitive price, but also focuses on excellent performance: high resolution images, broadband and multi-frequency transducers, abundant obstetrics/gynecology software packages, dual USB ports, 256-frame cine loop, 56MB build-in image storage and various storage forms, etc., all of which make clinical diagnosis more functional and convenient.

# DUS 8

## Digital Ultrasonic Diagnostic Imaging System

### Technical Specifications

#### General:

Imaging mode: B,B+B,4B, B+M,M

Gray scales: 256

Display: 14" non-interlaced

Transducer frequency: 2.0 ~ 10MHz

Transducer connector: 2 standard

Beam-forming: Digital Beam-forming  
Dynamic Receiving Focusing  
Real-time Dynamic Aperture  
Dynamic Frequency Scanning  
Dynamic Apodization  
Tissue Harmonic Imaging  
Tissue Specific Imaging

Scanning angle: from 30 to 155 degree (depending on transducers)

Scanning depth (mm): from 20 to 250 (depending on transducers)

#### Imaging Processing:

Pre-processing: Dynamic range  
Edge enhancement  
Frame correlation  
Line correlation  
Smooth  
AGC  
8-segment TGC adjustment  
IP (Image Process)

Post-processing: Gray map  
Gamma correction  
Rejection  
Left-right reverse  
Up-down reverse

#### Functions:

Cine loop: 256 frames bidirectional cine-loop  
Zoom: X1.0, X1.2, X1.4, X1.6, X2.0, X2.4, X3.0, X4.0 in distance  
Storage media: Built-in Flash, External USB-Memory stick  
Storage: 56MB permanent image  
Body mark: > 80 types  
Transducer auto-detection  
16-segment acoustic power output adjustment

#### Measurement & Calculation:

B-mode: distance, circumference, area, volume, angle,  
Ratio,%stenosis

M-mode: distance, time, velocity, heart rate (2 cycles), slope

Software packages: abdomen, gynecology, obstetrics, urology, small  
parts, cardiology, orthopedics

### Multi-frequency transducers



Convex array: C363-1



Micro-convex array: C321



Convex array: C343-1



Endovaginal: E613



Linear array: L743



Endorectal: E743

#### Display:

Date, Time, Probe Name, Probe Frequency, Frame Rate, Patient Name,  
Patient ID, Hospital Name, Measurement Values, Body Marks, Annotation,  
Probe Position, Full-image-region edit

#### Others:

Peripheral port: Video output 1  
VGA output port 1  
USB port 2  
DICOM3.0 1 (optional)  
Power supply: 100V-240V ~ 50Hz/60Hz  
Dimensions: 530mm(W) X 700mm(L) X 1300mm(H)  
Net weight: 33 kg

#### Standard Configurations:

DUS 8 main unit  
14" non-interlaced monitor  
Two transducer connectors  
256 frames cine loop memory  
56 MB built-in image storage  
Two USB ports  
Measurement & calculation software packages  
Convex array transducer: C363-1

#### Options:

Linear array transducer: L743  
Endorectal transducer: E743  
Endovaginal transducer: E613  
Micro-convex array transducer: C321  
Convex array transducer: C343-1

Video printer  
Laser printer  
Biopsy guide  
DICOM3.0  
Footswitch



Edan Instruments, Inc.

3/F - B, Nanshan Medical Equipments Park, Nanhai Rd 1019#, shekou, Nanshan Shenzhen, 518067 P.R. China  
Tel +68-755-26898326 Fax +86-755-26898330 www.edan.com.cn Email: info@edan.com.cn



All rights reserved.

Features and specifications are subject to change without notice

ENG-US-DUS8-V1.2-20091130